

# SafeBurn™ Odorant Flare



Rooted in Welker's commitment to creative, quality solutions, we engineered the SafeBurn™ to exceed your expectations. Safe, portable, and easy to use, the SafeBurn™ Odorant Flare is designed to burn off odorant vapors and blanket gases from tanks up to 1000 gallons prior to maintenance or decommissioning.

## Features

- Auto igniter
- Touch-safe heat shielding
- Flare gas check valve
- Mounted on two-wheel hand truck
- Hoses and fittings with carrying case included
- Corrosion-resistant materials

## Benefits

- Fast, easy, and safe pilot lighting
- Protect against burns
- Prevent the flame from backing up into the tank
- Modular, portable, and stable
- Quick and easy installation and operation
- Longer operational life



## SPECIFICATIONS

SAFEURN™ ODORANT FLARE

	OF-1 (4")	OF-2 (8")
Application	0–250 Gallon Odorant Supply Tank	0–1000 Gallon Odorant Supply Tank
Materials of Construction	Body and Trim: 316/316L Stainless Steel and Aluminum Seals: Viton® (Others Available)	
Maximum Allowable Flare Gas Inlet Pressure	1500 psig @ 10 °F to 100 °F	750 psig @ 10 °F to 100 °F
Maximum Allowable Pilot Gas Inlet	60 psig @ 10 °F to 100 °F	
Connections	Flare Gas Inlet: ¼" Quick-Connect Pilot Gas Inlet: ¼" Quick-Connect	Flare Gas Inlet: ½" Quick-Connect Pilot Gas Inlet: ¼" Quick-Connect
Flare Capacity	Up to 6 scfm	Up to 24 scfm
Burner Size	4"	8"
Mounting	Hand Truck	
Weight	Approx. 60 lb	Approx. 155 lb
Dimensions	48-½" (H) x 19-½" (W) x 20" (D)	60-½" (H) x 22-½" (W) x 28" (D)
Features	Auto Igniter Flare Gas Check Valve Flex Hoses With Valve and Quick-Connect Fittings in Carrying Case	

Weight and/or dimensions are approximate.  
Specifications subject to change without notice.

